

IMPORTANT DISCLAIMER: The below flow rates and operating ranges are based on consistent tip pressure. ALWAYS confirm pressure at spray tip corresponds with label requirements PRIOR to spraying any chemical. Proper maintenance and observation of system performance to maintain accurate pressures is recommended.



Spray Tip Charts[§] for Standard Spraying Systems for Spraying Engenia[™] Herbicide ¹

For use with **COMBO-JET®** Spray Tips

§Charts based on application of water with 20" nozzle spacing, with 110° spray angle tips

LEGEND:

(!) VERY IMPORTANT

TIP PRESSURE

Pressure (PSI) at the Tip
All required label rates and operating
criteria are based on required tip
pressure. Tip pressure creates the spray
pattern and droplet quality required for
spray application.

FLOW RATE

Flow Rate at Tip Pressure
The US Gallon/Minute flow rate of
water at the tip at stated pressure.

25-PS 15-0-MPH OUTSIDE REQ'D RANGE

Outside label requirements
If a cell is crossed out in red, it signifies
that the travel speed, pressure or droplet
category is outside the required operating
range by the chemical label.

OUTSIDE BOUNDS

Outside label requirements
If a cell is crossed out in black, it signifies
that the travel speed is out of bounds
due to other application factors like tip
pressure.



! UR Dual Chamber Spray Tip Series

Total baca onambor opidy rip conce								
SPRAY TIP PICTURE & PART #	Tip Pressure (PSI)	Class.	FLOW RATE (US GPM)	Sprayer Speed (MPH) at Application Rate (US GPA)				
UR110-05 PART#40292-05	Spec		tions	15 US GPA	20 US GPA			
UR 110 · 0; UR 110 · 0; Patent Pending -	25	UC	>>.46 <	Z.8-MPEL	5.9 MPH			
	30	UC	0.43	8.6 MPH	6.4 MPH			
	35	UC	0.47	9.3 MPH	6.9 MPH			
	40	UC	0.50	9.9 MPH	7.4 MPH			
	50	UC	0.56	11.1 MPH	8.3 MPH			
		UC		12:1 MPE	9.7-MPEL			
UR110-06 PART#40292-06	Spec		tions	15 US GPA	20 US GPA			
UR 110-0	25	UC	>>.4₹ <	9.4-MPH	Z:0-MPEL			
	30	UC	0.52	10.3 MPH	7.7 MPH			
	35	UC	0.56	11.1 MPH	8.3 MPH			
	40	UC	0.60	11.9 MPH	8.9 MPH			
	50	UC	0.67	13.3 MPH	10.0 MPH			
	60	UC	0.73	14.5 MPH	10.9 MPH			
UR110-08 PART#40292-08	Spec		tions	15 US GPA	20 US GPA			
UR 110 - 08	>25<	UC		12:5 MPEL	9.4 MPH			
	30	UC	0.69	13.7 MPH	10.3 MPH			
	35	UC	0.75	14.8 MPH	11.1 MPH			
	40	UC	0.80	15.8 MPH	11.9 MPH			
	50	UC	0.89	17.7 MPH	13.3 MPH			
	60	UC	0.98	19.4 MPH	14.5 MPH			
- Patent Pending -	70	UC	1.06	21.0 MPH	15.7 MPH			
UR110-10 PART#40292-10	Spec			15 US GPA	20 US GPA			
UR Dual Chamber	25<	UC		15.7 MPH	11.7 MPH			
DESIGN	30	UC	0.87	17.1 MPH	12.9 MPH			
	35	UC	0.94	18.5 MPH	13.9 MPH			
UR110·10	40	UC	1.00	19.8 MPH	14.9 MPH			
	50	UC	1.12	22.1 MPH	16.6 MPH			
	60	UC	1.22	24.2 MPH	18.2 MPH			
	70	UC	1.32	26.2 MPH	19.6 MPH			

! DR Single Pre-orifice Series

SPRAY TIP	Tip Pressure	FLOW RATE	Operating Speed (MPH) at Flow Rate (US GPA)	
PICTURE & PART #	(PSI)	(US GPM)	MPH @	MPH @
DR110-10 - PART#40286-10	Specifi	cations	15 US GPA	20 US GPA
DR SINGLE PRE-ORIFICE DESIGN DR 110 - 10	25	>0.79 <	15.7 MPH	11.7 MPH
	30	0.87	17.1 MPH	12.9 MPH
	35	0.94	18.5 MPH	13.9 MPH
	40	1.00	19.8 MPH	14.9 MPH
	50	> ₩	22.1 MPH	16.6 MPH

EXAMPLE APPLICATION

Example: 15 US GPA



UR110-06 @ 15 US GPA Operating Speed Range: 10.3 MPH @ 30PSI to 14.5 MPH @ 60PSI



Required Pre-orifices

Each DR & UR tip-caps include snap-in pre-orifices that MUST be used for proper spray operation. These pre-orifices are **NOT** interchangeable between sizes/ series of tip-cap.

(I) UR Dual Pre-orifices Series

The **UR series** tip-cap includes two snap-in orifices. One is short and snaps directly into the cap, the other is longer and snaps into the short orifice. NEVER operate UR series spray tips without BOTH orifices properly snapped in.





① DR Single Pre-orifice Series

The **DR series** tip-cap includes a single pre-orifice that snaps into the tip-cap.

NEVER operate DR series spray tips without the pre-orifice properly snapped in.



